

Customer: Lagear ENT CO LTD
Contact person: Robert Z Liu
EFBe Date of Order: 2012-08-09
Fax-No.: +886 4 25 39 19 73

Landabsatz 25, D-45731 Waltrop tel + 49 (0) 2309 78407-0 fax -10 info@efbe.de www.efbe.de

Testreport

Maximum load + Overload test Bicycle handlebar + stem Test item no. 123974

Test sample data

	nandlebar		stem
Manufacturer Model name	Lagear HB-MABR-35		Lagear None
Identity no.	None		None
weight (g)	428		220
Suspension		None	
Coating	Yes		Yes
Width / clamping width (mm)	775 / 675		
Clamping torque (Nm)	6		6
Clamping diameter (mm)	35		28,6
Length stem (mm)			50
Remarks	None		

Test description (LÜF_L)

Max./Overload test handlebar/stem EFBe left (LÜF_L)

The **test arrangement** is corresponding to EN 14766, clause 4.7.6.2. Load input is 50 mm from the <u>left bar end</u> parallel to the handlebar stem. The pneumatically applied test force is detected by the cylinder pressure with a precision pressure gauge. The measurement deviation is ±3 percent and the duration of force application is 10 s for maximum load and 1 second for overload. The permanent deformation is measured at the load input point in direction of the load.

EFBe-recommendations are:

A Maximum load test B Overload test

Load 1: 1 100 N Load 2: 1 500 N

max. perm. deformation: 10 mm Fracture behavior: no brittle fracture

Fracture behavior: no crack / fracture

Test result:

A Maximum load test: B Overload test:

Test load 1: 1 100 N Test load 2: 1 500 N
Permanent deformation: 4.7 mm Crack/fracture/deform.: Yes
Crack or fracture: No Brittle fracture: No

Remarks: For preceded tests please see testreport No. P1206028.

Test engineer: i.A. V. Stobberg

End of testing: 2012-08-16 Waltrop 2012-08-24

stamp, sign

This test report may not be reproduced but with complete wording. It contains the result of a one-time type testing and no statements about quality of serial production components are made. Readings of dimensions, torques and weights without engagement.

Testreport: P1206029 - 1 -